

Pigment Dispersions

Technical Data Sheet

Aurasperse[®] Carbon Black W-7012



These high-quality organic and inorganic colorants can be used for water-based and emulsion systems with pH values ranging from 7 to 11, and can be intermixed.

Chemical Nature

An aqueous dispersion of Color Index Pigment Black 7.



Masstone

1:5

1:20

Properties

Typical Properties

	Pigment	Total
Solids by Weight	33 %	46 %
Solids by Volume	20 %	57 %
Viscosity		80 - 90 KU
pH		9.0 – 10.0
Density at 20 °C		1.2 g/cm ³
Boiling Point		> 100 °C
Weight per gallon		10.1 lbs/gal
Hegman Grind		6 min.

Applications

Aurasperse[®] Carbon Black W-7012 is used in the following applications:

- Consumer Paint
- Rubber Latex
- Non-woven fabrics
- Lumber marking
- Cement
- Paper coatings

Aurasperse[®] and Aurasperse[®] II dispersions are controlled for tint strength with a tolerance of +/- 3% versus master standards with strong batch-to-batch color consistency. Aurasperse[®] and Aurasperse[®] II have cost-effective, high performance characteristics.

Aurasperse[®] dispersions are conventional pigment dispersions consisting of water, pigment, surfactants, and preservatives. Aurasperse II dispersions are free of alkylphenol ethoxylates (APEs).

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet Aurasperse® Carbon Black W-7012.

Storage

Aurasperse® Carbon Black W-7012 has a shelf life of 1 year from the date of manufacture for material in original, unopened, properly stored containers. Beyond 1 year, we recommend the quality of the material be confirmed prior to use by retesting the certificate of analysis parameters.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.** Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Aurasperse is a registered trademark of BASF Group.

© BASF Corporation, 2016



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.

For more information on Responsible Care® go to:

U.S.: www.basf.us/responsiblecare_usa

Canada: www.basf.us/responsiblecare_canada

México: www.basf.us/responsiblecare_mexico

BASF Corporation
Dispersions and Resins
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
Email: edtech_info@basf.com
www.basf.us/dpsolutions