

Pigment Dispersions

Technical Data Sheet



Aurasperse® W-6014 FC Green SP

These high-quality organic and inorganic colorants can be used for water-based and emulsion systems with pH values ranging from 7 to 11, and can be intermixed.

Chemical Nature

An aqueous dispersion of Color Index Pigments Green 17 and Black 11

Properties

Typical Properties

Pigment content by weight	%	55 - 75
pH		8.5 – 10.0
Viscosity	KU	90 - 105
Specific gravity	g/cm ³	2 - 3
Density	lbs/gal	16.7 – 25.0
Hegman Grind		6 (minimum)

Applications

Aurasperse® colorants are used in the following applications:

- Consumer paint
- Rubber latex
- Non-woven fabrics
- Lumber marking
- Cement
- Paper coatings

Features

Aurasperse® and Aurasperse® II dispersions are controlled for tint strength with a tolerance of +/- 3% versus master standards with strong batch-to-batch color consistency. Aurasperse® and Aurasperse® II have cost effective, high performance characteristics.

Aurasperse® dispersions are conventional pigment dispersions consisting of water, pigment, surfactants and preservatives. Aurasperse® II dispersions are free of alkylphenol ethoxylates (APEs).

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Aurasperse® W-6014 FC Green SP.

Storage

Aurasperse® W-6014 FC Green SP has a shelf life of 1 year from the date of manufacture for material in original, unopened, properly stored containers. Beyond 1 year, we recommend the quality of the material be confirmed prior to use by retesting the certificate of analysis parameters.

Important

The descriptions, designs, and data contained herein are presented for your guidance only. Because there are many factors under your control which may affect processing or application/use it is necessary for you to make appropriate tests to determine whether the product is suitable for your particular purpose prior to use. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, OR DATA MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, DATA OR DESIGNS PROVIDED BE PRESUMED TO BE A PART OF OUR TERMS AND CONDITIONS OF SALE.** Further, you expressly understand and agree that the descriptions, designs, and data furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for same or results obtained from use thereof, all such being given to you and accepted by you at your risk.

Aurasperse is a registered trademark of BASF Group.

© BASF Corporation, 2015



BASF Corporation is fully committed to the Responsible Care® Initiative in the USA, Canada, and Mexico.
For more information on Responsible Care® go to:
U.S.: www.basf.us/responsiblecare_usa
Canada: www.basf.us/responsiblecare_canada
México: www.basf.us/responsiblecare_mexico

BASF Corporation
Dispersions and Resins
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
Email: edtech_info@basf.com
www.basf.us/dpsolutions