

# Foamaster<sup>®</sup> MO NXZ

(old: Foamaster<sup>®</sup> NXZ)



<b>general</b>	liquid defoamer for emulsion paints and adhesive systems
<b>chemical nature</b>	formulation based on hydrocarbons and non-ionic surfactants

---

## Properties

<b>physical form</b>	turbid amber liquid						
<b>shelf life</b>	When stored under the usual appropriate storage conditions, the product can be stored for 1 year.						
<b>typical properties (no supply specification)</b>	<table><tr><td>water content</td><td>~ 0.25%</td></tr><tr><td>density at 20 °C (68 °F)</td><td>~ 0.87 g/cm<sup>3</sup></td></tr><tr><td>Brookfield viscosity at 23 °C (73 °C)</td><td>~ 450 mPa . s</td></tr></table>	water content	~ 0.25%	density at 20 °C (68 °F)	~ 0.87 g/cm <sup>3</sup>	Brookfield viscosity at 23 °C (73 °C)	~ 450 mPa . s
water content	~ 0.25%						
density at 20 °C (68 °F)	~ 0.87 g/cm <sup>3</sup>						
Brookfield viscosity at 23 °C (73 °C)	~ 450 mPa . s						

---

## Application

Foamaster<sup>®</sup> MO NXZ is a defoamer for emulsion paints based on styrene-butadiene, acrylic, polyvinyl chloride and its copolymers, ethylene-vinyl acetate, vinylidene chloride and water-soluble alkyds.

<b>recommended concentrations</b>	<table><tr><td>paints</td><td>0.2 – 0.0 % on total formulation</td></tr><tr><td>adhesives</td><td>0.5 – 1.0 % on latex solids</td></tr></table>	paints	0.2 – 0.0 % on total formulation	adhesives	0.5 – 1.0 % on latex solids
paints	0.2 – 0.0 % on total formulation				
adhesives	0.5 – 1.0 % on latex solids				

Foamaster<sup>®</sup> MO NXZ can be incorporated as supplied or after emulsifying in water. Best results are obtained if half of the defoamer is added prior to grinding and the remainder at the let-down stage.

**Safety**

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

**Note**

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of the BASF Group, unless otherwise noted

BASF SE  
Formulation Additives  
67056 Ludwigshafen, Germany  
[www.dispersions-pigments.basf.com](http://www.dispersions-pigments.basf.com)  
[formulation-additives-asia@basf.com](mailto:formulation-additives-asia@basf.com)  
[formulation-additives-europe@basf.com](mailto:formulation-additives-europe@basf.com)  
[formulation-additives-nafta@basf.com](mailto:formulation-additives-nafta@basf.com)  
[formulation-additives-south-america@basf.com](mailto:formulation-additives-south-america@basf.com)