Color Pigment Dispersion

Technical Data Sheet

PureOptions™ J

We create chemistry

PureOptions[™] eco-colorants – BASF's expanded colorant line for paint suppliers seeking to produce environmentally responsible products in their point-of-sale (POS) tinting operations.

Chemical Nature	Organic Pigment Dispersion			
	2 oz	4 oz	8 oz	12 oz
	Properties			
Typical Properties	Pigment, Vol. Pigment, Wt. Solids, Vol. Solids, Wt.		18 % 40 % 48 % 63 %	
	Specific gravity Viscosity (KU) Density		1.4 75 <u>+</u> 8 12.0 lbs/gal	
	VOC (per ASTM D6886) (per U.S. EPA Method	24)	<50 g/L 0 g/L	

Applications

Features

As an advanced approach to colorant technology, PureOptions[™] enable a wide range of paint colors to be created with < 50g/l VOC content, per the more stringent ASTM D 6886 test method. Designed for optimal paint performance, PureOptions[™] colorants retain critical properties such as gloss, color reproducibility, and block resistance without adding VOC content.

PureOptions[™] is packaged in our patent-pending plastic container allowing for efficient transfer of the product into POS dispensers. Simply open the screw-top lid and pour the color into the dispenser. In only one minute, 97% of the contents will be drained from the container. To avoid waste, simply close the container with the same re-sealable lid to avoid contamination or spillage.

PureOptions[™] eco-colorants help our customers to realize sustainable, VOC- and APEO-free paint formulations that do not compromise on performance, enabling them to compete for new lines of business. As the world's leading chemical company, BASF can help you deliver eco-responsible paint solutions that meet or exceed performance requirements. We are putting together the right resources to make your products better and help you to be more successful.

Safety

GeneralThe usual safety precautions when handling chemicals must be observed. These include the
measures described in Federal, State and Local health and safety regulations, thorough ventilation of
the workplace, good skin care and wearing of protective goggles.

Material Safety Data Sheet All safety information is provided in the Material Safety Data Sheet PureOptions™ J.

Storage

PureOptions[™]J has a shelf life of up to 1 year from the date of manufacture for material in original, unopened, properly stored containers. Beyond 1 year BASF recommends the quality of the material be confirmed prior to use by retesting the certificate of analysis parameters.

Important

While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, they are provided for guidance only. Because many factors may affect processing or application/use, BASF recommends that the ready make tests to determine the suitability of a product for a particular purpose prior to use. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF THE BASF TERMS AND CONDITIONS OF SALE. Further, the descriptions, designs, data and information furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for the description, designs, data or information given or results obtained all such being given and accepted at the reader's risk.

PureOptions is a trademark of BASF Group.

© BASF Corporation, 2015



BASF Corporation is fully committed to the Responsible Care[®] initiative in the USA, Canada, and Mexico. For more information on Responsible Care[®] goto: U.S.: www.basf.us/responsiblecare_usa Canada: www.basf.us/responsiblecare_canada México: www.basf.us/responsiblecare_mexico

BASF Corporation 100 Park Avenue Florham Park, NJ 07932 Tel: (800) 962 – 7829 Fax: (800) 971 – 1123 Email: edtech_info@basf.com www.basf.us/dpsolutions