

Proprietary Lubricant / North America

Glycolube® TS is a specialty lubricant suggested for use in styrenics, ABS, modified ABS engineering resins, and copolymers with minimal effect on final properties. It imparts good pressability and excellent mold release at use levels of 0.5 – 2.0 phr.

Physical Properties

Acid Value (mg KOH/g)	4 Max.
Color, Gardner 1963	1 Max

Specifications and analytical methods are available upon request.

Typical Properties

Appearance	White Beads*
------------	--------------

*Glycolube™ TS tends to agglomerate and it is more pronounced in high temperature, high humidity conditions.

Packaging

Leverpak, lined drums, 200 pound net weight.

Fiberpak, 40 pounds net weight

Manufacturing Location

Williamsport, PA

FDA Status

Permitted for use under the following FDA 21 CFR Guidelines:

176.170 – Components of Paper and Paperboard in contact with aqueous and fatty foods.

176.180 - Components of Paper and Paperboard in contact with dry food.

176.210 – Defoaming agents used in manufacture of paper and paperboard.

177.2800 – Textile and Textile Fibers

182.70 – Substances migrating from cotton and cotton fabrics used in dry food packaging.

For questions or for further information please e-mail Technical Sales Support at:

contact.allendale@arxada.com