

# Efka<sup>®</sup> FL 3337

(old : Efka<sup>®</sup> FL 3037)



The Chemical Company

## general

slip and leveling agent

- prevents surface defects like cratering, scarring or blistering in air-drying and baking finishes
- shortens setting time
- prevents cob-webbing in baking enamels
- prevents streaking during painting and spraying of chlorinated rubber and coatings based on other chlorinated polymers
- prevents chilling of nitrocellulose lacquers

## chemical nature

blend of high-boiling aromatic hydrocarbons, ketones and esters, including a highly compatible polysiloxane

---

## Properties

### physical form

clear, colorless liquid

### shelf life

The product should be stored in a cool dry place. When kept in its original unopened containers, it will keep up to 4 years.

### typical properties (no supply specification)

solvent	see <i>chemical nature</i> above
density at 20 °C (68 °F)	~ 0.86 g/cm <sup>3</sup>
refractive index	~ 1.482
flash point	42 °C (108°F)

---

## Application

Efka<sup>®</sup> FL 3337 can be used in solvent-based coating systems.

### recommended concentrations

3–5% on total formulation

Efka<sup>®</sup> FL 3337 can be added either during or after batch preparation.

**Safety**

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

**Note**

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of the BASF Group, unless otherwise noted

BASF SE  
Formulation Additives  
67056 Ludwigshafen, Germany  
[www.dispersions-pigments.basf.com](http://www.dispersions-pigments.basf.com)  
[formulation-additives-asia@basf.com](mailto:formulation-additives-asia@basf.com)  
[formulation-additives-europe@basf.com](mailto:formulation-additives-europe@basf.com)  
[formulation-additives-nafta@basf.com](mailto:formulation-additives-nafta@basf.com)  
[formulation-additives-south-america@basf.com](mailto:formulation-additives-south-america@basf.com)