### **Technical Data Sheet**





general

- member of a novel series of defoamers based on patented FoamStar<sup>®</sup> technology
- very fast bubble break versus conventional defoamers
- effective in industrial coatings based on acrylic emulsions
- good persistence

chemical nature

defoamer based on patented FoamStar® technology and mineral oil

# **Properties**

**physical form** opaque, off-white liquid

storage FoamStar® ST 2400 should always be stored in tightly closed

containers. Store in a cool place.

If subjected to below freezing temperatures, FoamStar® ST 2400 may congeal or stratify. Warm to 122°F (50°C) and mix well before use.

typical properties dispersibility (10% in water) non-dispersible

density ~ 7.2 lbs/gal viscosity ~ 700 cps

# **Application**

FoamStar® ST 2400 will be equally effective in both the grind and the letdown.

- non-separating and non settling
- effective in industrial coatings based on acrylic emulsions
- very fast bubble break versus conventional defoamers
- effective against micro- and macro foam
- good persistence

## recommended concentrations

a dosage of 0.25-0.5% calculated on total formulation is recommended for effective defoaming.

#### Contacts worldwide

Asia

BASF East Asia Regional Headquarters Ltd

45/F, Jardine House No. 1 Connaught Place Central Hong Kong

China

formulation-additives-asia@basf.com

Europe BASF SE

Formulation Additives 67056 Ludwigshafen

Germany

formulation-additives-europe@basf.com

North America **BASF** Corporation 11501 Steele Creek Road Charlotte, NC 28273

USA

formulation-additives-nafta@basf.com

South America BASF S.A

Rochaverá - Crystal Tower Av. das Naçoes Unidas, 14.171 Morumbi - São Paulo-SP

Brazil

formulation-additives-south-america@basf.com

Validity
This Technical Data Sheet is valid for all versions of the FoamStar ST 2400: FoamStar ST 2400, FoamStar ST 2400 NC.

Safety
When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

### Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and

www.basf.com\formulation-additives

 $<sup>^{\</sup>circledR}$  = registered trademark,  $^{\intercal M}$  = trademark of BASF Group, unless otherwise noted