Printing & Packaging

Technical Data Sheet

Joncryl® LMV 7051



Product Description

Joncryl® LMV 7051 is a low maintenance vehicle, pH-stable, non-film forming, Rheology Controlled (RC) acrylic emulsion for printing ink applications.

Key Features & Benefits

- Low pH maintenance

- Excellent resolubility

- High gloss and holdout

Chemical Composition

RC acrylic emulsion

Properties

Typical Properties

Appearance opaque emulsion Non-volatile at 145°C (2g, 30 min) $\sim 45\%$

pH at 25°C $$\sim 7.8$$ Viscosity at 25°C (#2 LV, 30 rpm, 30 sec) $$\sim 7.8$$ $\sim 200-700$ cps

 Molecular weight (Mw)
 > 200,000

 Acid number (NV)
 115

 Density at 25°C
 1.04 g/cm³

 MFFT
 56°C

 Tg
 98°C

Freeze-thaw stable Yes
Total VOC 0.3% wt

These typical values should not be interpreted as specifications.

Applications

Joncryl® LMV 7051 is a low maintenance, pH-stable, non-film forming, RC acrylic emulsion that provides high gloss and holdout in ink formulations for paper and paperboard substrates. This product can be used to formulate high performance inks that do not rely on press-side modifications of pH with ammonium hydroxide or organic amines and is compatible with a wide range of formulation components.

The combination of good drying speed and excellent resolubility of Joncryl® LMV 7051 allows the formulator to produce high gloss inks that produce sharp line work and precise process dots.

Joncryl® LMV 7051 is recommended for applications such as:

· Printing inks for flexographic or gravure applications

December 2016 Rev 3 Page 1 of 2

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measures described in Federal, State, and Local health and safety regulations, thorough ventilation of the workplace, good skin care, and wearing of protective googles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Joncryl® LMV 7051.

Important

While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, they are provided for guidance only. Because many factors may affect processing or application/use, BASF recommends that the reader make tests to determine the suitability of a product for a particular purpose prior to use. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. In no case shall the descriptions, information, data or designs provided be considered a part of BASF's terms and conditions of sale. Further, the descriptions, designs, data, and information furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for the descriptions, designs, data or information given or results obtained all such being given and accepted at the reader's risk.

Joncryl is a registered trademark of BASF Group.

© BASF Corporation, 2016



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico. For more information on Responsible Care® go to: U.S.: www.basf.us/responsiblecare_usa Canada: www.basf.us/responsiblecare canada México: www.basf.us/responsiblecare mexico

U.S & Canada

BASF Corporation 24710 W Eleven Mile Road Southfield, MI 48033 ph: 1(800) 231-7868 fax:1(800) 392-7429

Email: Custserv_charlotte@basf.com Email: edtech_info@basf.com www.basf.us/dpsolutions

Mexico

BASF Mexicana, S.A. de C.V. Av. Insurgentes Sur # 975 Col. Ciudad de los Deportes C.P. 03710 Mexico, D.F. Phone: (52-55) 5325-2756

Fax: (52-55) 5723-3011

December 2016 Rev 3