

KaMin LLC 822 Huber Road Macon GA 31217 Main 478-750-5410 www.kaminsolutions.com



Product Description

Ultrex HP is a very fine particle sized calcined kaolin with high brightness. It has been dehydroxylated to remove water of crystallization. It has been pulverized to provide ease of dispersion.

Application Information

Ultrex HP is recommended for use in various coatings and plastics applications. In coatings it provides a very high degree of opacity and tint strength. In filled plastics and rubber, it provides good reinforcement along with possibility of TiO₂ reduction.

Physical Properties	Typical Value	
Physical Form	Powder	
Special Modifications	None	
GE Brightness (%)	93	
Screen Residue, 325 Mesh (%)	0.01	
Free Moisture (%) measured at 105°C	0.5	
pH (20% solids)	5	
Specific Gravity (g/cm³)	2.63	
Bulk Density, Loose lb/ft³ (kg/m³)	13 / 210	
Bulk Density, Tamped lb/ft3 (kg/m3)	20 / 320	
Oil Absorption, Rubout (ASTM D-281)	115	

Revised April 2021 ©2022

KaMin® LLC, KaMin® and the KaMin® logo are registered trademarks of KaMin® LLC The above data are representative data for this product and should not be perceived as specifications or maximum/minimum values. The information contained herein is believed to be accurate and reliable, but KaMin® MAKES NO WARRANTIES OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR ANY OTHER EXPRESS OR IMPLIED WARRANTY. The information herein relates only to the specific product described and not to such product in combination with any other product. Providing information as herein contained is not to be regarded by implication or otherwise as conveying any rights or permission for use which would violate any patent rights or violate any law, safety code or insurance regulation. Natural mineral products are subject to the normal variations related to the deposits from which they are mined.