

TufCOR® 580 Emulsion

Description:

- TufCOR® 580 is a vinyl based emulsion polymer.
- This polymer exhibits outstanding water/alkali resistance.
- Provides excellent adhesion to a variety of porous and non-porous substrates.
- Excellent formulation latitude and good tackifier response.
- Films of this emulsion are inherently flexible and exhibit a high degree of dry tack.

Suggested Applications:

- General purpose construction adhesives
- Flooring adhesives

Storage & Handling:

- Shelf life is approximately six months at 77° F.
- Consult MSDS for important health, safety and handling information before using this product.
- Consult Celanese's *Storing, Handling and Preserving Emulsion Products* brochure.

Typical Properties	
Solids	62-64%
Viscosity ¹	<1000 cps
pH	4.0 – 5.0
Tg (°C)	-18
Density	8.5 lbs/gal
Mechanical stability	Excellent

¹ Brookfield RVF, @ 77°F



Version: April 2014

8040 Dixie Highway, Florence, KY 41042 • Technical Service 877-832-7782 • Customer Service: 800-845-0940
emulsionstechservice@celanese.com • www.celanese-emulsions.com

Copyright © 2014. Celanese or its affiliates. All rights reserved.

This publication was printed based on Celanese's present state of knowledge, and Celanese undertakes no obligation to update it. Because conditions of product use are outside Celanese's control, Celanese makes no warranties, express or implied, and assumes no liability in connection with any use of this information. Nothing herein is intended as a license to operate under or a recommendation to infringe any patents.

© 2014 Celanese, [the C-ball design] and [TufCOR] are registered trademarks of Celanese or its affiliates.