

**Description:**

- A vinyl-based emulsion designed for use in interior painter's caulk. The emulsion allows for good adhesion to multiple substrates, including wood and cement, and is ideal for dry, interior applications.

**Features:**

- Excellent filler acceptance
- Good adhesion
- Freeze-thaw stability
- Excellent gunnability and finish

**Suggested Applications:**

- Caulks and sealants
- Spackling compounds

**Storage & Handling:**

- Shelf life is approximately six months at 77° F.
- Consult MSDS for important health, safety and handling information before using this product.
- Consult Celanese's *Storing, Handling and Preserving Emulsion Products* brochure.

Typical Properties	
Solids	47%
Viscosity <sup>1</sup>	100 cps
pH	6.0
Mechanical stability	Excellent
Freeze-thaw stable	Yes

<sup>1</sup> Brookfield RVF-20 RPM, #3, @ 77°F

Typical Film Properties	
Clarity	Hazy
Tg (°C)	+3-
Water resistance	Fair



**Version: April 2014**

8040 Dixie Highway, Florence, KY 41042 • Technical Service 877-832-7782 • Customer Service: 800-845-0940  
emulsionstechservice@celanese.com • www.celanese-emulsions.com

Copyright © 2014. Celanese or its affiliates. All rights reserved.

This publication was printed based on Celanese's present state of knowledge, and Celanese undertakes no obligation to update it. Because conditions of product use are outside Celanese's control, Celanese makes no warranties, express or implied, and assumes no liability in connection with any use of this information. Nothing herein is intended as a license to operate under or a recommendation to infringe any patents.

® 2014 Celanese, [the C-ball design] and [TufCOR] are registered trademarks of Celanese or its affiliates.