

**Description:**

- A crosslinking emulsion copolymer for use in interior and exterior wood bonding applications. When properly crosslinked with meet ASTM D3110 and Type II/D3 specifications
- Applications may include: Construction adhesives, wood bonding, subfloor, etc.

**Features:**

- Provides excellent adhesion to hardwood
- Excellent water resistance
- Interior and exterior uses
- Hydrophobic
- Low residual VAM

**Storage & Handling:**

- Shelf life is approximately six months at 77° F.
- Consult MSDS for important health, safety and handling information before using this product.

- Consult Celanese's *Storing, Handling and Preserving Emulsion Products* brochure.

**Typical Properties**

Solids	49%
Viscosity <sup>1</sup>	3500 – 7500 cps
pH	4.2 – 5.2
Density	9.0 lbs/gal
Borax compatible	No
Freeze-thaw stable	Yes
Plasticizer response (avg)	1.9

<sup>1</sup> Brookfield RVF, @ 77°F

**Typical Film Properties**

Tg (°C)	+30
Water Resistance	Excellent

**Version: April 2014**

8040 Dixie Highway, Florence, KY 41042 • Technical Service 877-832-7782 • Customer Service: 800-845-0940  
emulsionstechservice@celanese.com • www.celanese-emulsions.com

Copyright © 2014. Celanese or its affiliates. All rights reserved.

This publication was printed based on Celanese's present state of knowledge, and Celanese undertakes no obligation to update it. Because conditions of product use are outside Celanese's control, Celanese makes no warranties, express or implied, and assumes no liability in connection with any use of this information. Nothing herein is intended as a license to operate under or a recommendation to infringe any patents.

© 2014 Celanese, [the C-ball design] and [TufCOR] are registered trademarks of Celanese or its affiliates.