

INEOS Pigments 6752 Baymeadow Drive Glen Burnie, MD 21060

Tel: +1 (410) 229-4400 Fax: +1 (410) 229-4415 www.ineos.com

RCL**696** Coatings

Description:	RCL696 is a high performance, superdurable chloride-process rutile titanium dioxide pigment. It offers a unique combination coupling maximum chalk resistance, excellent gloss and gloss retention with high opacity and ease of dispersion.	
Key Features:	 Excellent chalk resistance Excellent gloss retention High tint strength and gloss 	 Exceptional whiteness Superior dispersibility Manufacturing consistency
Applications:	RCL696 is recommended for evaluation in:	
	 Coil coatings Marine and protective coatings Powder coatings Automotive, OEM and refinishing systems 	 Industrial maintenance coatings Low VOC/high solids formulations Organosols and plastisols
Typical Properties:	 TiO₂ content: 92% Surface treatment: alumina, silica, organic Oil absorption: 21g/100g pH (10% suspension): 7.9 Specific gravity: 4.0 Density: 33.3 lbs/gal 	
Additional Information:	 RCL696 conforms to: ASTM D476 Type IV and Type V BS EN ISO 591-1:2000 Type R2 ECOIN: listed under EINECS number 236-675-5 CAS number 13463-67-7 Color Index 77891, Pigment White 6 NSF Certification 	
Regulatory Status:	Due to the wide range of applications for RCL696, this subject is too diverse to cover adequately in a technical datasheet. Declarations of conformity, including food contact compliance, can be provided on request. Please contact your INEOS Pigments sales representative.	

Unless otherwise provided by applicable law, nothing contained in this literature shall be deemed a representation or warranty of any kind, either expressed or implied. The recommendations and suggestions given in this literature are presented for your own investigation and verification. The products of INEOS Pigments, its subsidiaries and affiliates ("Seller") are sold only on the basis of conforming to specifications, and subject to Seller's standard Terms and Conditions of Sale, but without warranty, expressed or implied, in law or in fact, of merchantability or fitness for a particular purpose and upon the condition that purchasers make their own tests to determine the suitability of such products for their particular purposes. Statements concerning the possible use of Seller's products or processes described are not intended as recommendations or permission to use the same in the infringement of any patent, or to practice a patented invention without a license. By reason of a lack of knowledge as to specific end uses of this product, no representation or warranty is made as to the conformance of the product with food contact laws or regulations.

See the Safety Data Sheet (SDS) for this product for safety information prior to use.

This document does not constitute a specification. Product Specifications are available on request.