

# HYPOX<sup>®</sup> RM22 CTBN-Toughened Epoxidized Cyclohexane Dimethanol Adduct

## Product Description

HYPOX<sup>®</sup> RM22 is an adduct of CTBN with epoxidized cyclohexane dimethanol. Compared to standard epoxy resin/CTBN adducts, the product exhibits a moderate viscosity, coupled with a high rubber content. HYPOX<sup>®</sup> RM22 adduct is intended for use in combination with standard epoxy resins when the end-use application requires toughening and improved rubber compatibility with DGEBA. HYPOX<sup>®</sup> RM22 adduct will increase flexibility, crack, fatigue and peel resistance, and adhesive properties. It will also improve the cathodic disbondment property when use in coating formulations for underground buried pipes for oil and gas transport applications

## Applications

- Adhesives
- Encapsulating
- Potting
- Coatings
- Toughening of prepregs and composites

## Typical Properties

Property	HYPOX <sup>®</sup> RM20
Appearance	Clear, Clean
Viscosity at 25°C, cP	15,000 – 25,000
Epoxide Equivalent Weight, g/eq	320 – 360
Gardner Color, max	10
Weight per Gallon at 25°C, lb.	8.6 ± 0.1
CTBN content, %	50% HYPRO <sup>®</sup> 1300X13

## Storage

**HYPOX<sup>®</sup> RM22** adduct should be stored in a dry place, in the sealed original containers, at temperatures between **+2°C and +40°C (+35.6°F and +104°F)**. Under these storage conditions, the product has a shelf life of **24 months** (from date of manufacture). The products should not be exposed to direct sunlight.

## Precautionary Statement

Huntsman Advanced Materials Americas LLC maintains up-to-date Safety Data Sheets (SDS) on all of its products. These sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products. Users should review the latest SDS to determine possible health hazards and appropriate precautions to implement prior to using this material.

### First Aid!

Refer to SDS as mentioned above.

**KEEP OUT OF REACH OF CHILDREN**

**FOR PROFESSIONAL AND INDUSTRIAL USE ONLY**

## Important Legal Notice

Sales of the product described herein (“Product”) are subject to the general terms and conditions of sale of either Huntsman Advanced Materials LLC, or its appropriate affiliate including without limitation Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials Americas Inc., or Huntsman Advanced Materials (Hong Kong) Ltd. (“Huntsman”). The following supercedes Buyer’s documents.

Huntsman warrants that at the time and place of delivery all Products sold to Buyer shall conform to the specifications provided to Buyer by Huntsman.

While the information and recommendations included in this publication are, to the best of Huntsman’s knowledge, accurate as of the date of publication, NOTHING CONTAINED HEREIN (EXCEPT AS SET FORTH ABOVE REGARDING CONFORMANCE WITH SPECIFICATIONS PROVIDED TO BUYER BY HUNTSMAN) IS TO BE CONSTRUED AS A REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND THE BUYER ASSUMES ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES.

No statements or recommendations made herein are to be construed as a representation about the suitability of any Product for the particular application of Buyer or user or as an inducement to infringe any patent or other intellectual property right. Buyer is responsible to determine the applicability of such information and recommendations and the suitability of any Product for its own particular purpose, and to ensure that its intended use of the Product does not infringe any intellectual property rights.

The Product may be or become hazardous. The Buyer should obtain Material Safety Data Sheets and Technical Data Sheets from Huntsman containing detailed information on Product hazards and toxicity, together with proper shipping, handling and storage procedures for the Product, and should comply with all applicable governmental laws, regulations and standards relating to the handling, use, storage, distribution and disposal of, and exposure to the Product. Buyer shall also take all steps necessary to adequately inform, warn and familiarize its employees, agents, direct and indirect customers and contractors who may handle or be exposed to the Product of all hazards pertaining to and proper procedures for safe handling, use, storage, transportation and disposal of and exposure to the Product, and the containers or equipment in which the Product may be handled, shipped or stored.

**HYPOX®** is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all countries.

**Copyright © 2020 Huntsman International LLC.**

### **Customer Support Center:**

**Huntsman Corporation**  
10003 Woodloch Forest Dr  
The Woodlands, TX 77380  
Tel: +1 (888) 564-9318  
Fax: +1 (281) 719-6416  
www.huntsman.com