

POLYPHASE® 763CR

Dry-Film Preservative

Paints & Coatings/US

EPA Registration No.: 5383-109

Polyphase® 763CR is a broad-spectrum, water-based product that is effective against a wide variety of fungal and algal organisms where controlled release of active ingredients is beneficial.

Application & Use

Polyphase® 763CR features a controlled release algaecide for enhanced leach resistance. The synergistic combination of actives in this product outperforms many single active based formulations. Polyphase® 763CR offers excellent dry-film protection against fungal and algal growth on paints, masonry coatings, stucco, and pigmented water-based wood protective stains. Polyphase® 763CR also provides excellent protection against fungal and algal growth on caulks, sealants, and joint cements.

Product Highlights

- Controlled release algaecide for longer lasting protection
- Broad-spectrum performance
- Highly effective against a variety of fungal & algal organisms
- Does not chalk on exposure
- Color stable in white paint

Physical Properties

The following are typical properties of Polyphase® 763CR; they are not to be considered product specifications.

| Appearance: | Off-white, creamy dispersion |
|-------------------------|------------------------------|
| Specific Gravity, 25°C: | 1.14 |
| pH (as is) | 6.5 |
| Viscosity, 25°C | 1200 |

Formulating Considerations

Field testing of final products under actual use conditions is strongly recommended. All suggested use applications should be evaluated for final product efficacy, color uniformity, and for pH, temperature, and storage stability. Metal containers for formulated products should always be lined. Do not store formulated products for prolonged periods in iron or steel containers. Due to various possibilities of application and different methods of processing, it is advised to check compatibility in the development of new products. Contact your Arxada representative for assistance.

Shelf-life is 12 months from date of manufacture.

Active Substance

| 15.0% (<1% Free) | 3-(3,4-dichlorphenyl)-1,1-dimethylurea | Diuron | $CI \longrightarrow N \longrightarrow Diuron \\ C_9H_{10}CI_2N_2O$ |
|---------------------|--|--------|--|
| 9.0% | Methyl 2-benzimidazolecarbamate | BCM | O BCM OCH ₃ C ₉ H ₉ N ₃ O ₂ |
| 3.0% | 3-lodo-2-propynyl butyl carbamate | IPBC | O IPBC C ₈ H ₁₂ INO ₂ |

Paints & Coatings/US 1 | P a g e

Function/Activity

The following suggested use levels are based on laboratory tests and are typical for the applications indicated. The actual level required for your system is formulation specific. The selection of the individual components of the formulation, the substrate to be coated, and the environment in which the coating will be exposed all have an influence on the amount of protection needed. Suggested use levels are reported as percentage of the end-use product.

Paint and Coatings

Polyphase® 763CR has been shown to be an excellent control agent against fungi and algae in water-based paints and coatings. In hot, humid areas where mold and mildew are a particularly severe problem, the higher application levels are suggested. Polyphase® 763CR should be added at the end after final pH adjustments have been made (not during the grind).

Wood Protective Stains (Water-Based)

Polyphase® 763CR offers broad-spectrum protection against the discoloration of the protective film due to fungi and algae. Polyphase® 763CR does not change the appearance of wood or have any influence on its coatability. Polyphase® 763CR is recommended only for pigmented wood stains. For clear and semitransparent stains, performance tests should be conducted to ensure that Polyphase® 763CR does not affect the transparency of the final coating.

Caulks and Sealants

Polyphase® 763CR can be used to prevent the growth of fungal and algal organisms in wet and cured caulks and sealants. Polyphase® 763CR should be added towards the end of the production cycle with good agitation.

| Function | % Wt/Wt |
|------------------------|--------------|
| Paint | 0.70 - 2.00% |
| Wood Protective Stains | 0.50 - 2.00% |
| Masonry Coatings | 0.20 - 0.60% |
| Roof Coatings | 0.70 - 3.00% |
| Caulks & Sealants | 0.50 - 1.50% |
| Stucco | 0.50 - 1.50% |
| Joint Cements | 0.50 - 1.20% |

Packaging

Polyphase® 763CR is packaged in:

| Package Type | Net Weight |
|--------------|------------------|
| Pail | 40 lbs / 18.1 kg |
| Small Drum | 66 lbs / 29.9 kg |
| Large Drum | 463 lbs / 210 kg |

Product Safety & Additional Information

For handling, storage, health, and safety information and disposal procedures, as well as additional information, please refer to the Safety Data Sheet (SDS) and label.

arxada

For more information visit: www.arxada.com

Use biocides safely. Always read the label and product information before use. All product information corresponds to Arxada's knowledge on the subject at the date of publication, but Arxada makes no warranty as to its accuracy or completeness and Arxada assumes no obligation to update it. Product and safety information is intended for use by recipients experienced and knowledgeable in the field. who are capable of and responsible for independently determining the suitability of ingredients for intended uses and to ensure their compliance with applicable law. Proper use of this information is the sole responsibility of the recipient. Republication of this information or related statements is prohibited. Information provided by Arxada is not intended and should not be construed as a license to operate under or a recommendation to infringe any patent or other intellectual property right. No claims are made herein for any specific intermediate or end-use application. The information contained in this document is proprietary and confidential. The recipient shall keep this document strictly secret using at least the same level of measures as it uses to protect its own confidential information, but in any case at least commercially reasonable own confidential information, © 2023 Arxada Ltd. but in any case at least commercially reasonable and

customary efforts. The recipient shall use this document only for the purpose specified in the applicable contractual documentation between the recipient and Arxada and will not make any use of it for its own separate benefit or the benefit of any third party. The use by other persons or entities than the intended recipient is prohibited. If you receive this transmission in error, please contact Arxada immediately and delete this document and its attachments from your system. Upon termination of the applicable contractual relationship between the recipient and Arxada, the recipient shall return or destroy promptly this document. Recipient shall at any time be fully liable for any and all breaches of the confidentiality duty and indemnify Arxada for any damages derived thereunder. Recipient acknowledges that the information provided is considered a trade secret and therefore the duty of confidentiality must remain in force for an undetermined period of time, regardless of any prior contractual agreement with Arxada. All trademarks belong to their respective owners or to Arxada as acknowledged.

Paints & Coatings/US **2** | P a g e